## BANNER LOCATIONS AND INSTALLATION GUIDELINES

	Post <u>Mile</u>	Distance Between <u>Poles</u>	Length of Ropes (including <u>banner)</u>	Maximum Banner <u>Length</u>
1. Sepulveda Blvd. & Marine Avenue	23.42	92 ft.	38 ft.	30 ft.
2. Manhattan Avenue & 12 <sup>th</sup> Place		63 ft.	38 ft.	30 ft.
<ol> <li>Manhattan Avenue &amp; 9<sup>th</sup> Street</li> </ol>		63 ft.	38 ft.	30 ft.
4. Highland Avenue & 13 <sup>th</sup> Place		43 ft.	38 ft.	30 ft.
5. Highland Avenue n/o 11 <sup>th</sup> Street		43 ft.	38 ft.	30 ft.
<ol> <li>Manhattan Beach Blvd e/o Morningside Dr.</li> </ol>		64 ft.	38 ft.	30 ft.

- 1. Banners shall be a minimum length of ten (10) feet and shall be only thirty-six (36) inches maximum in width.
- 2. Banners shall have brass grommeted holes at each corner and across the top at 24-inch maximum intervals. Grommets shall have an opening of 3/8 inch. A triangular shaped piece of substantial fabric, a minimum of 12 inches on two sides, shall be double stitched into each corner before the four corner grommets are installed.
- 3. Rope shall be a minimum <sup>1</sup>/<sub>2</sub> inch diameter and in good condition, free from defects. Rope shall be sewn into the top and bottom of the banner.
- 4. Half-moon air holes should be cut several times throughout the banner (to prevent wind damage).

Attachment #4

(updated 01/10/11)