



NOTES

1. CONCRETE SHALL BE CLASS 560-C-3250 PCC, CURED WITH WHITE PIGMENTED CURING COMPOUND.
2. ALL EXPOSED CORNERS SHALL BE FINISHED WITH $\frac{1}{2}$ " RADIUS.
3. FINISH SHALL BE FINE BROOM.
4. EXISTING PCC SHALL BE SAWCUT AT SCORELINE PRIOR TO REMOVAL.
5. CURBS SHALL HAVE EXPANSION JOINTS AT 60' INTERVALS, AND WEAKENED PLANE JOINTS AT 10' INTERVALS ONLY; NO SCORELINE ALLOWED.
6. WHEN ROLLED CURB IS PLACED BY AN EXTRUSION MACHINE, FINISHING WORK SHALL PROVIDE AN ACCEPTABLE FINISH AND WEAKENED PLANE JOINTS MAY BE SAWCUT.
7. ROLLED CURB MAY BE USED WITH THE APPROVAL OF THE CITY ENGINEER.
8. WHERE IT APPLIES, INTEGRAL COLORED CONCRETE SHALL BE PALM SPRING TAN BY COLORFUL CONCRETE PRODUCTS OR EQUAL.



DATE REVISED

04-24-2019

**CITY OF MANHATTAN BEACH
DEPARTMENT OF PUBLIC WORKS**

TYPE C ROLLED CURB

APPROVED BY

PREM KUMAR, CITY ENGINEER

DATE

STANDARD PLAN NUMBER

MBSI-121A-0

SHEET 1 OF 1