

## **MANHATTAN BEACH FIRE DEPARTMENT**

400 15th STREET, MANHATTAN BEACH, CALIFORNIA 90266

Fire Prevention (310) 802-5206 Fax (310) 802-5201

## **FIRE PREVENTION BUREAU**



## FIRE LIFE/SAFETY INSPECTION

Notice of conditions not in compliance with Local and/or State Fire Safety Regulations					
Initial	Inspection:	Reinspection #:	Business Na	me:	
Date:			Business Ad	dress:	
		Shift:	Business Ph	one:	
			Business Lic	ense:	
1. Address Numerals & Business License					
	☐ ABL01 CFC 505 New and existing buildings shall have approved address numbers visible from the street or road fronting the proper				
2.					
	FPE01 Title 19	Fire extinguishers shall be maint	Fire extinguishers shall be maintained in a fully charged and operable condition and kept in their designated places.		
	FPE02 Title 19	Fire extinguishers shall be serviced annually or immediately after use.			
	FPE03 CFC 904	Commercial kitchen hood systems are required to be serviced semi-annually or after activation of the system.			
	FPE04 CFC 609	Hoods, grease removal devices, fans and ducts over cooking surfaces in kitchens shall be cleaned at intervals.			
	FPE05 Title 19	Automatic sprinkler systems and standpipes shall have current 5 year certification.  Fire Department Connections (FDC) shall be maintained unobstructed by fences, bushes, trees or walls at all times.			
	FPE06 CFC 912 FPE07 CFC 903	All valves controlling automatic sprinkler systems shall be electrically supervised by a listed fire alarm control unit.			
	FPE08 CFC 509	Fire protection equipment shall be identified by signs and access shall be maintained for all fire protection equipment.			
	FPE09 CFC 506	It is the responsibility of the building owner to maintain and update Knox Box keys.			
3.					
	ELC01 CFC 605				
	ELC02 CFC 605	Extension cords & flexible cords shall not be substitute for permanent wiring, affixed to structures, extended through			
	walls, ceilings or floors, or under doors. Extension cords shall be used only with portable appliances.				
	ELC03 CFC 605	Multiplug adapters, unfused plug strips or cube adapters not complying with the 2010 CEC shall be prohibited.			
	ELC04 CFC 605	Open junction boxes and open wiring splices shall be provided with an approved cover on all switches and outlets.			
	ELC05 CFC 605	Minimum 30" inches clearance shall be provided in front of electrical panels with no storage obstructing access.			
	4. Clearances & Exits				
	EXT01 CFC 315 EXT02 CFC 315	Storage shall be maintained 2' feet or more below the ceiling in nonsprinklered areas of buildings.  Maintain a minimum of 18" inches below sprinkler head deflectors in sprinklered areas of buildings.			
	EXT02 CFC 315 EXT03 CFC 304	All storage shall be kept in an orderly manner and rubbish shall be disposed immediately.			
	EXT04 CFC 1017	Aisles in Group B & M occupancies shall not be less than 36" inches in width.			
	EXT05 CFC 1027	All exit doors shall provide a direct and unobstructed access to a public way.			
	EXT06 CFC 1011	Exits and exit access doors shall be marked by an approved exit sign readily visible from any direction of egress travel.			
	EXT07 CFC 1011	Illuminated exit signs shall be illuminated at all times. Exit signs shall have two sources of power.			
	EXT08 CFC 1025	Fire doors in horizontal exits (corridors) shall be self-closing or automatic-closing when activated by a smoke detector.			
	EXT09 CFC 703	Hold-open devices and automatic door closers shall be maintained. Out-of-service doors for repairs shall remain closed.			
	EXT10 CFC 1030	Exit accesses, exits or exit discharges shall be continuously maintained free from obstructions or impediments.			
	EXT11 CFC 1008	Egress doors shall be readily openable from the egress side without the use of a key or special knowledge or effort.			
5.					
	The procedure decorated and a constraint of the process of the constraint of the process of the				
	HAZ02 CFC 304	Materials susceptible to spontaneous combustion, such as oily rags, shall be stored in a listed disposal container.			
	HAZ03 CFC 1504	Clean or replace spray booth filters. Discarded filters shall be placed in a noncombustible container.			
	HAZ04 CFC 304 Structural	Combustible waste material creating a fire hazard shall not be allowed to accumulate in buildings or upon premises.			
6.					
"	coatings and sprayed fire-resistant materials) shall be maintained and properly repaired, restored or replaced when damaged, altered, breached or penetrated.				
	☐ STR02 CFC 316 Trapdoors and scuttle covers shall be kept closed at all times except when in use.				
□ No Violations Observed – Thank You!					
Additional Violations and Violation Description Remarks:					
Occupancies Over 2000 Square Feet					
				Square Footage:	
L					
				Width:	
				The state of the s	
				Property Use:	
A Compliance Inspection will be made on or about:					
Receiv	Received by:Title:				
Signature: Date:  Distribution: White; Fire Prevention Yellow; Business Revised 02/2016					
Distribut	ion: White: F	Tre Prevention Ye	ellow; Business	Revised 02/2016	

2139

Revised 02/2016